



PCD1-AA90TNR

IR IP Dome Camera

PCD1-AA90TNR

IR IP VF Dome Camera

- 2M IP Camera
- Small-Case : 112pi x 87mm x 81pi
- Lens : 2.7mm ~ 12mm
- Iris : DC Iris (Galvanometer)
- TDN : Galvanometer
- IR LED : 5pi 24EA MAX 10M (Center)
- Visible Ray : View Angle 90°
- Protocol : OnVif
- DC 12V

Spec

Items	Sub-itmes	PCD1-AA90TNR
Lens	Back Focal Length	2.7~12mm±5%
	Iris	DC Iris (Galvanometer)
	TDN	Day & Night (Galvanometer)
I/O	Control	UART0
Power Consumption		DC +12V
Operation Temperature		Absolute : -10°C ~ +50°C
Operation Humidity		Less than 90%
Dimension		112pi x 87 x 81pi
CMOS	Device	1/2.8" 2MEGA CMOS
	Total	1945 (H) × 1109 (V)
	Effective	1945 (H) × 1097 (V)
Performance	Horizontal/Vertical Resolution	1920x1080
	Minimum illumination	Color : 0.03 Lux(50IRE) / 0.06 Lux(15IRE) B/W : 0.25 Lux(50IRE) / 0.05 Lux(15IRE)
	S/N Ratio	More than 50dB (AGC off)
	Frame	30FPS Full HD
Functions	OSD	Off/On
	Day&Night	Auto/Color/B&W/EXTERN
	ATW	1800 ~ 10500K
	High Speed Shutter	1/60(1/50) ~ 1/135Ksec
	WDR	Off/ON
	Blemish Compensation	Auto detection & correction
	BLC	Off/ON
	HLC	Off/ON
	AGC	Max 54dB
	White Balance	ATW, Shade, Clear Sky, Fluorescent Light ETC.
	DNR	2D+3DNR
	Motion Detection	Off/ON
	De-Fog	Off/On
	Lens Distortion Compensation	Off/On


IP (Network)

Items	Sub-items	Description
Video	Compression	H.264(High, Main, Base line profile), MJPEG
	Resolution	1920x1080(Full-HD)
	Frame Rate	Up to 30fps@1920x1080p
Streaming		Simultaneously H.264 and MJPEG (Triple Streaming)
		Independent Frame Rate and Bandwidth Control, VBR/CBR Mode
FTP	Uploading	MJPEG Still Image
Security		Multi User Authority, IP Filtering, HTTPS
Network Time Sync		Synchronize Computer/NTP Server, Manual
Software Reset		Restart, Reset, Factory Default
Auto Recovery		Restore
Remote Upgrade		Using Web Browser
Protocols		TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf
Client Software		Built-In Web, ONVIF Compatible 3rd Party VMS
Max. User Connection		4 Users
SDK Support		API, ONVIF Profile S Compliant

Cable Configuration



Dimension



PCD1-AA90TNR

*Design and specifications are subject to change without notice.

P&A CORPORATION
www.pnacorp.co.kr

[Customer Center] T. +82) 31-212-5760 F. +82) 31-212-5761
VSS Dept. : #503,97, Jungbu-daero 448beon-gil, Yeongtong-gu, Suwon-si,
Gyeonggi-do, Korea, 16521